



Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

**Motor magnético permanente, velocidad variable,
acoplado directo doble tapa**

HQ-30 TPM

MODEL	PSI	CFM
HQ-30 TPM	100	148
	125	144
	145	123
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		18
Noise Level		72±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		22
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	160
	Width (cm)	90
	Height (cm)	150
Weight (Kg)		730
Outlet Diameter		1 1/2"



HQ-50 TPM

MODEL	PSI	CFM
HQ-50 TPM	100	254
	125	250
	145	222
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		54
Noise Level		72±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		37
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	170
	Width (cm)	110
	Height (cm)	160
Weight (Kg)		1080
Outlet Diameter		1 1/2"





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ-60 TPM

MODEL	PSI	CFM
HQ-60 TPM	100	346
	125	342
	145	275
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		72
Noise Level		72±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		45
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	210
	Width (cm)	140
	Height (cm)	185
Weight (Kg)		1980
Outlet Diameter		2"



HQ-75 TPM

MODEL	PSI	CFM
HQ-75 TPM	100	452
	125	441
	145	339
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		90
Noise Level		75±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		55
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	210
	Width (cm)	140
	Height (cm)	185
Weight (Kg)		2180
Outlet Diameter		2"





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ-100 TPM

MODEL	PSI	CFM
HQ-100 TPM	100	618
	125	582
	145	441
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		90
Noise Level		75±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		75
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	230
	Width (cm)	145
	Height (cm)	195
Weight (Kg)		2280
Outlet Diameter		2"



HQ-125 TPM

MODEL	PSI	CFM
HQ-125 TPM	100	734
	125	699
	145	596
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		110
Noise Level		75±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		90
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	290
	Width (cm)	220
	Height (cm)	196
Weight (Kg)		3200
Outlet Diameter		DN80





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ-150 TPM

MODEL	PSI	CFM
HQ-150 TPM	100	865
	125	829
	145	695
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<Ambient Temperature 40°C
Oil Capacity		110
Noise Level		75±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		110
Electricity		440V/3PH/60Hz
Dimension	Lenght (cm)	290
	Width (cm)	220
	Height (cm)	196
Weight (Kg)		3360
Outlet Diameter		DN80



HQ- 175 TPM

MODEL	PSI	CFM
HQ- 175 TPM	100	1059
	116	988
	145	829
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		125
Noise Level		82±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		132
Power		440V/3F/60Hz
Dimension	Lenght (cm)	290
	Width (cm)	220
	Height (cm)	196
Weight (Kg)		3450
Outlet Diameter		DN80





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ-200 TPM

MODEL	PSI	CFM
HQ- 200 TPM	100	1218
	116	1186
	145	1059
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		125
Noise Level		82±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		160
Power		440V/3F/60Hz
Dimension	Lenght (cm)	280
	Width (cm)	220
	Height (cm)	196
Weight (Kg)		3850
Outlet Diameter		DN80



HQ- 250 TPM

MODEL	PSI	CFM
HQ- 250 TPM	100	1447
	116	1356
	145	1147
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		150
Noise Level		82±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		185
Power		440V/3F/60Hz
Dimension	Lenght (cm)	350
	Width (cm)	210
	Height (cm)	210
Weight (Kg)		3990
Outlet Diameter		DN100





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ- 285 TPM

MODEL	PSI	CFM
HQ- 285 TPM	100	1575
	116	1518
	145	1359
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		150
Noise Level		82±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		200
Power		440V/3F/60Hz
Dimension	Lenght (cm)	350
	Width (cm)	210
	Height (cm)	210
Weight (Kg)		5890
Outlet Diameter		DN100



HQ- 300 TPM

MODEL	PSI	CFM
HQ- 300 TPM	100	1716
	116	1659
	145	1479
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		180
Noise Level		84±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		220
Power		440V/3F/60Hz
Dimension	Lenght (cm)	380
	Width (cm)	210
	Height (cm)	265
Weight (Kg)		6500
Outlet Diameter		DN100





Udara Air Compressors
Hermosillo, Sonora, México
Tel: 662 216 1995
contacto@udaracompressors.com

HQ- 350 TPM

MODEL	PSI	CFM
HQ- 350 TPM	100	1942
	116	1906
	145	1624
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		180
Noise Level		84±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		250
Power		440V/3F/60Hz
Dimension	Lenght (cm)	380
	Width (cm)	210
	Height (cm)	265
Weight (Kg)		6800
Outlet Diameter		DN125



HQ- 380 TPM

MODEL	PSI	CFM
HQ- 380 TPM	100	2189
	116	2118
	145	1801
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		110
Noise Level		84±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		280
Power		440V/3F/60Hz
Dimension	Lenght (cm)	400
	Width (cm)	212
	Height (cm)	220
Weight (Kg)		7200
Outlet Diameter		DN125





Udara Air Compressors
 Hermosillo, Sonora, México
 Tel: 662 216 1995
contacto@udaracompressors.com

HQ- 425 TPM

MODEL	PSI	CFM
HQ- 425 TPM	100	2295
	116	2189
	145	1942
Cooling Type		Air Cooling
Exhaust Temperature (°C)		<40
Oil Capacity		110
Noise Level		84±2 dB(A)
Driving Mode		Direct Drive
Power (HP)		315
Power		440V/3F/60Hz
Dimension	Lenght (cm)	435
	Width (cm)	212
	Height (cm)	220
Weight (Kg)		7800
Outlet Diameter		DN125

